



## COMPRESSION FITTINGS

Compression fittings for PEX and Multilayer pipes are installation systems simple and safe for plumbing and heating nets.

### SERVICE CONDITIONS

|                    |  |
|--------------------|--|
| Nominal pressure:  | 16 bar   |
| Test pressure:     | 25 bar   |
| Temperature range: | cold and hot water up to 95°C                              |
| Fluid:             | water intended to human consumption and domestic hot water |

### MAIN CONSTRUCTIVE FEATURES

#### ONE FITTING FOR TWO TUBES

ARCO compression fittings are designed to be assembled with ARCOPEX or ARCOKAPA systems.

#### LEAK TIGHTNESS SYSTEM

The nozzle and the main body of the fitting is one piece component, therefore there is no possibility of leakage between these two parts.

The joint between the pipe and fitting is guaranteed by two O-rings and a brass sleeve, which avoid any displacement of the tube.

### PRODUCT RANGE

MALE STRAIGHT FITTING



FEMALE STRAIGHT FITTING



STRAIGHT FITTING



REDUCING STRAIGHT FITTING



FEMALE ELBOW



WALL PLATE ELBOW



MALE ELBOW



ELBOW



FEMALE TEE



TEE



REDUCING TEE



## OTHER CONNECTION SYSTEMS OF ARCO

### PRESS FITTING - ARCOPEX® & ARCOKAPA®



### COPPER FITTING



### BRASS COMPRESION FITTING FOR PE TUBE



### BRONZE FITTING



Válvulas ARCO, s.l.  
Avda. del Cid, 8  
46134 Foios (Valencia / Spain)  
[www.valulasarco.com](http://www.valulasarco.com)

Commercial Export:  
tel. (+34) 961 499 429  
fax. (+34) 961 499 428  
[export@valulasarco.es](mailto:export@valulasarco.es)

